

The ExSol package*

Walter Daems (`walter.daems@uantwerpen.be`)

1 Introduction

1.1 Package goal

The package ExSol provides macros to allow embedding exercises and solutions in the $\text{\LaTeX}$ source of an instructional text (e.g., a book or a course text) while keeping the exercises and the solutions separately in the typeset result.

In *global mode* (the default), this corresponds to generating the following separate documents:

- your original text that only contains the exercises, and
- a solution book that only contains the solutions to the exercises (a package option exists to also copy the exercises themselves to the solution book).

The former is generated when running $\text{\LaTeX}$ on your document. This run writes the solutions to a secondary file that can be included into a simple document harness, such that when running $\text{\LaTeX}$ on the latter, you can generate a nice solution book.

In *external mode* both the exercises and the solutions are written to secondary files that can be included in a simple document harness, such that when running $\text{\LaTeX}$ on these, you can generate an exercise as well as a solution book.

In *local mode* (invoked by specifying the package option 'local'), this corresponds to inserting the saved solutions in the current document at a later stage in the text.

In *inline mode* (invoked by specifying the package option 'inline'), the solutions are inserted 'on the spot'.

This has been conveniently summarized in the table below:

mode	exercises	solutions
global	on the spot	in separate document
external	in separate document	in separate document
local	on the spot	later in the same document
inline	on the spot	on the spot

*This document corresponds to exsol 1.7, dated 2025/02/14.

1.2 Why use ExSol?

- It allows to keep the $\text{\LaTeX}$ source of your exercises and their solutions together in a single file, next to each other. Away with the nightmare to keep your solutions in sync with the exercises!
- It separates exercises and solutions, allowing you
 - to only release the solution book to the instructors of the course (using global mode);
 - to encourage students to first try solving the exercises without peeking into the list of solutions (or the solution book).

1.3 Credits

The code of the EXSOL package was taken almost literally from `fancyvrb` [1]. Therefore, all credits go to the authors/maintainers of `fancyvrb`.

Thanks to Paul Levrie, Pieter Pareit, Pekka Pere, Benjamin Grinstein and Philippe Marti for signaling problems and making suggestions for the improvement of the package and the documentation.

1.4 Note

As of version 1.2, the package also contains facilities for generating a formula collection. The only limitation is that exercises and solutions cannot be part of the formula collection. Though this is a restriction, it is not a severe one in my opinion. Formula collections should be as concise as they can be.

Though generating formula collections goes beyond exercises and solutions, I chose not to change the package's name EXSOL. Einstein's name was also not changed into Relativistic Einstein when he got to understand the theory of relativity.

2 Installation

Either you are a package manager and then you'll know how to prepare an installation package for EXSOL.

Either you are a normal user and then you have two options. First, check if there is a package that your favorite $\text{\LaTeX}$ distributor has prepared for you. Second, grab the TDS package from CTAN [2] (`exsol.tds.zip`) and unzip it somewhere in your own TDS tree, regenerate your filename database and off you go. In any case, make sure that $\text{\LaTeX}$ finds the `exsol.sty` file.

The EXSOL package uses some auxiliary packages: `fancyvrb`, `ifthen`, `kvoptions` and, optionally, `babel`. Fetch them from CTAN [2] if your $\text{\TeX}$ distributor does not provide them.

3 Usage

3.1 Preparing your document source

3.1.1 Loading the package

The macro package `exsol` can be loaded with:

```
\usepackage{babel}  
\usepackage{exsol}
```

Note before we start that you need to load the `babel` package before you load the `exsol` package! This is to allow you to load the appropriate languages for your text.

OK, now let's get started.

Your first choice to make is where you want your solutions to appear. The primary objective of the `exsol` package was 'global mode', i.e. separating your solutions from the exercises, gathering the solutions in a separate book. To this end, don't specify the package option '`[local]`', or specify '`[local=false]`'.

A second mode of operation is 'local mode'. This allows grouping your exercises in series and including them later in your text. Gathering exercises in (numbered) series and 'loading' them locally in your text, allows for simplifying the individual exercise numbers (omitting their prefix containing, chapter number, section number, subsection number a.s.o.).

A third mode of operation is 'inline mode', in which the solution is inserted in the main text 'on the spot'. You can trigger this, by specifying the package option '`inline`'.

3.1.2 Global mode - flat grouping exercises

Adding exercises together with their solutions in your document is easy. Just embed them in a `exercise` and a corresponding `solution` environment. Optionally, you may embed several of them in a `exercises` environment to make them stand out in your text.

```
\begin{exercises}[columns=2]  
  
  \begin{exercise}  
    Calculate  $y = 5 + 7$   
  \end{exercise}  
  \begin{solution}  
     $y = 12$   
  \end{solution}  
  
  \begin{exercise}  
    Calculate  $y = 7 - 12$ 
```

```

\end{exercises}
\begin{solution}
  $y = -5$
\end{solution}

\end{exercises}

```

The optional argument of the `exercises` environment allows specifying the typesetting in multiple columns.

On how to generate a solution book, take a look at the examples in section [3.2.1](#).

3.1.3 Local mode - grouping of exercises in series

One might also consider to keep the solutions in the same text, in local mode. In this case, we advise to gather the exercises in series (e.g. according to their degree of difficulty). This can be done by using the `exerciseries` environment instead of the `exercises` environment. This environment takes and also takes a mandatory label argument. In addition it takes two optional arguments:

- `columns` to specify the amount of columns
- `exsubrule` to specify the creation of a horizontal rule below the exercise series.
- `solsubrule` to specify the creation of a horizontal rule below the solution series.
- `subrule` to specify the creation of a horizontal rule below the exercise and the solution series.

```

\begin{exerciseries}[columns=2,subrule=\hrule]{Easy exercises}

  \begin{exercise}
    Calculate $y = 5 + 7$
  \end{exercise}
  \begin{solution}
    $y = 12$
  \end{solution}

  \begin{exercise}
    Calculate $y = 7 - 12$
  \end{exercise}
  \begin{solution}
    $y = -5$
  \end{solution}

\end{exerciseries}

\begin{exerciseries}{Difficult exercises}

```

```

\begin{exercise}
  Calculate  $y = 5 \cdot 7$ 
\end{exercise}
\begin{solution}
 $y = 35$ 
\end{solution}

\begin{exercise}
  Calculate  $y = 8 / 4$ 
\end{exercise}
\begin{solution}
 $y = 2$ 
\end{solution}

\end{exerciseseries}

```

As an alternative, you can specify the 'inline' option to include the solutions on the spot where you specified them.

3.2 Examples

3.2.1 Global mode

Below, you can find an example of a file that contains a number of exercises and solutions, with the goal to generate a separate solution book. Note that referencing exercises works just as you would expect it.

```

%<*example>
\documentclass[a4paper,10pt]{article}

\usepackage{a4wide}
\usepackage[english]{babel}
\usepackage[copyexercisesinsolutions]{exsol}

\title{Gobal example, from the \textsf{ExSol} package}
\author{Walter Daems}
\setlength{\parindent}{0em}
\begin{document}
\maketitle

\section{Introduction}

In this text we explain how to solve second-order polynomial
equations.

\section{Solving second-order polynomial equations}

\begin{informulacollectiononly}
\section*{Solving second-order polynomial equations}
\end{informulacollectiononly}
\begin{informulacollection}
  The roots of the following equation
  \begin{equation}
    ax^2 + bx + c = 0
  \end{equation}

```

```

\end{equation}
can be determined as:
\begin{equation}
x_{1,2} = \frac{-b \pm \sqrt{b^2 - 4 a c}}{2 a}
\end{equation}
\end{informatiacollection}

```

To make sure you master calculating the roots of second-order equation, please solve exercise \ref{ex:1}.

```

\begin{exercises}[columns = 2]

\begin{exercise}
\label{ex:1}
Solve the following equation for  $x \in \mathbb{C}$ , with  $\mathbb{C}$  the set of
complex numbers:
\begin{equation}
5x^2 - 3.1x = 5
\end{equation}
\end{exercise}
\begin{solution}
Let's start by rearranging the equation, a bit:
\begin{equation}
5.7x^2 - 3.1x - 5.3 = 0
\end{equation}
The equation is now in the standard form:
\begin{equation}
ax^2 + bx + c = 0
\end{equation}
For quadratic equations in the standard form, we know that two
solutions exist:
\begin{equation}
x_{1,2} = \frac{-b \pm \sqrt{d}}{2a}
\end{equation}
with
\begin{equation}
d = b^2 - 4ac
\end{equation}
If we apply this to our case, we obtain:
\begin{equation}
d = (-3.1)^2 - 4 \cdot 5.7 \cdot (-5.3) = 130.45
\end{equation}
and
\begin{equation}
x_1 = \frac{3.1 + \sqrt{130.45}}{11.4} = 1.27 \\
x_2 = \frac{3.1 - \sqrt{130.45}}{11.4} = -0.73
\end{equation}
The proposed values  $x = x_1, x_2$  are solutions to the given equation.
\end{solution}
\begin{exercise}
\label{ex:2}
Consider a 2-dimensional vector space equipped with a Euclidean
distance function. Given a right-angled triangle, with the sides
 $AB$  and  $BC$  adjacent to the right angle having lengths,  $3$  and
 $4$ , calculate the length of the hypotenuse, labeled  $AC$ .
\end{exercise}
\begin{solution}
This calls for application of Pythagoras' theorem, which
tells us:
\begin{equation}

```

```

\left\|A\right\|^2 + \left\|B\right\|^2 = \left\|C\right\|^2
\end{equation}
and therefore:
\begin{eqnarray}
\left\|C\right\|
&=& \sqrt{\left\|A\right\|^2 + \left\|B\right\|^2}\\
&=& \sqrt{3^2 + 4^2}\\
&=& \sqrt{25} = 5
\end{eqnarray}
Therefore, the length of the hypotenuse equals 5$.
\end{solution}
\end{exercises}

And now, we can come to the conclusion.
\section{Conclusion}
Solving second-order polynomial equations is very easy.
\end{document}
%</example>

```

The result in the original document, can be seen in the file `example.pdf`. As you can see, the `formulacollection` entry and the exercise appear. There's no trace of the solution.

The solution can be recovered by including the `example.sol.tex` file in an appropriate harness. This is explained in section [3.2.3](#).

3.2.2 external mode

Below, you can find an example of a file that contains a number of exercises and solutions, with the goal to generate a separate exercise and solution book.

```

%<*example-external>
\documentclass[a4paper,10pt]{article}

\usepackage{a4wide}
\usepackage[english]{babel}
\usepackage[external]{exsol}

\title{External example, from the \textsf{ExSol} package}
\author{Walter Daems}
\setlength{\parindent}{0em}
\begin{document}
\maketitle

\section{Introduction}

In this text we explain how to solve second-order polynomial
equations.

\section{Solving second-order polynomial equations}

\begin{informulacollectiononly}
\section*{Solving second-order polynomial equations}
\end{informulacollectiononly}
\begin{informulacollection}
The roots of the following equation
\begin{equation}
a x^2 + bx + c = 0

```

```

\end{equation}
can be determined as:
\begin{equation}
x_{1,2} = \frac{-b \pm \sqrt{b^2 - 4 a c}}{2 a}
\end{equation}
\end{informulacollection}

\begin{exercises}[columns = 2]

\begin{exercise}
Solve the following equation for  $x \in \mathbb{C}$ , with  $\mathbb{C}$  the set of
complex numbers:
\begin{equation}
5 x^2 - 3.1 x = 5
\end{equation}
\end{exercise}
\begin{solution}
Let's start by rearranging the equation, a bit:
\begin{equation}
5.7 x^2 - 3.1 x - 5.3 = 0
\end{equation}
The equation is now in the standard form:
\begin{equation}
a x^2 + b x + c = 0
\end{equation}
For quadratic equations in the standard form, we know that two
solutions exist:
\begin{equation}
x_{1,2} = \frac{-b \pm \sqrt{d}}{2a}
\end{equation}
with
\begin{equation}
d = b^2 - 4 a c
\end{equation}
If we apply this to our case, we obtain:
\begin{equation}
d = (-3.1)^2 - 4 \cdot 5.7 \cdot (-5.3) = 130.45
\end{equation}
and
\begin{equation}
x_1 = \frac{3.1 + \sqrt{130.45}}{11.4} = 1.27 \\
x_2 = \frac{3.1 - \sqrt{130.45}}{11.4} = -0.73
\end{equation}
The proposed values  $x = x_1, x_2$  are solutions to the given equation.
\end{solution}
\begin{exercise}
Consider a 2-dimensional vector space equipped with a Euclidean
distance function. Given a right-angled triangle, with the sides
 $A$  and  $B$  adjacent to the right angle having lengths,  $3$  and
 $4$ , calculate the length of the hypotenuse, labeled  $C$ .
\end{exercise}
\begin{solution}
This calls for application of Pythagoras' theorem, which
tells us:
\begin{equation}
|A|^2 + |B|^2 = |C|^2
\end{equation}
and therefore:
\begin{equation}
|C| = \sqrt{|A|^2 + |B|^2}
\end{equation}

```



```

&= & \sqrt{3^2 + 4^2} \\
&= & \sqrt{25} = 5
\end{eqnarray}
Therefore, the length of the hypotenuse equals $5$.
\end{solution}
\end{exercises}
And now, we can come to conclusion.

\section{Conclusion}
Solving second-order polynomial equations is very easy.
\end{document}
%</example-external>

```

The result in the original document, can be seen in the file `example-external.pdf`. As you can see, only the `formulacollection` entry appears. There's no trace of the exercises or the solutions.

3.2.3 Harnesses

When running $\text{\LaTeX}$ on your document in global or external mode (e.g., the file `example-external.tex` as part of the `exsol` package, as a side effect files with the extension `.sol.tex`, `.exc.tex` and/or `.fc.tex` have been written to disk (in our case, the files `example-external.sol.tex`, `example-external.exc.tex` and `example-external.fc.tex`), containing all exercises, solutions and entries for the formula collection in sequence.

Generating an exercises/solution book is as simple as including the exercise/solution file into a simple $\text{\LaTeX}$ harness, that allows you giving it a proper title page and to add other bells and whistles. As an example, you can find a harness for a solution book below.

```

%<*examplesol>
\documentclass[a4paper,10pt]{article}

\usepackage{a4wide}
\usepackage[english]{babel}
\usepackage{exsol}

\setlength{\parindent}{0em}

\title{Solutions to the exercises, specified in the example of the
\textsf{ExSol} package}
\author{Walter Daems}

\begin{document}

\maketitle

\input{example.sol.tex}

\end{document}
%</examplesol>

```

Similar harnesses can be used for the exercise book and the formula collection.

```

%<*examplefor>
\documentclass[a4paper,10pt]{article}

\usepackage{a4wide}
\usepackage[english]{babel}
\usepackage{exsol}

\setlength{\parindent}{0em}

\title{Formula collection, specified in the example of the
\textsf{ExSol} package}
\author{Walter Daems}

\begin{document}

\maketitle

\input{example.fc.tex}

\end{document}
%</examplefor>

%<*exampleexc>
\documentclass[a4paper,10pt]{article}

\usepackage{a4wide}
\usepackage[english]{babel}
\usepackage{exsol}

\setlength{\parindent}{0em}

\title{Exercise book, specified in the example-external of the
\textsf{ExSol} package}
\author{Walter Daems}

\begin{document}

\maketitle

\input{example-external.exc.tex}

\end{document}
%</exampleexc>

```

3.2.4 Local mode

Below, you can find an example of a file that contains a number of exercises and solutions, with the goal to include them later in the same document. This is done by issuing the `loadSolutions` macro at the very end of the file. This macro can be called multiple times and will gobble up and include all solutions so far. As a consequence the solutions file is emptied and can be filled again by specifying new exercise/solution pairs.

```

%<*example-local>
\documentclass[a4paper,10pt]{article}

\usepackage{a4wide}
\usepackage[german]{babel}

```



```

entstehenden Kosten  $y$  (in Franken) zuordnet?

\item Berechne, bei welcher Arbeitszeit die Kosten bei beiden
Firmen gleich sind.
\end{enumerate}
\end{exercise}
\begin{solution}
\begin{enumerate}[label=\alph*)]
\item Firma A: 308.-  $\text{\$}$  Firma B: 315.-
\item A:  $y=76x+42\text{\$}$  B:  $y=80x+35\text{\$}$ 
\item Bei  $\frac{3}{4}$  Stunden
\end{enumerate}
\end{solution}
\end{exerciseseries}

\section{\solutionsname}
\loadSolutions

\end{document}
%</example-local>

```

3.2.5 Inline mode

Below, you can find an example of a file that contains a number of exercises and solutions, with the goal to include the solutions on the spot.

```

%<*example-inline>
\documentclass[11pt,a4paper]{article}

\usepackage[german]{babel}
\usepackage[inline,usesolutionserieslabels]{exsol}
\usepackage{enumitem}

\setlength{\exsolexercisetopbottomsep}{0pt plus 0pt minus 1pt}
\setlength{\exsolexercisefleftmargin}{2em}
\setlength{\exsolexerciserightmargin}{1em}
\setlength{\exsolexerciseparindent}{0em}
\setlength{\exsolexerciselabelsep}{1ex}
\setlength{\exsolexerciselabelwidth}{30pt}
\setlength{\exsolexerciseitemindent}{0pt}
\setlength{\exsolexerciseparsep}{\parskip}

\title{Local inline example, from the \textsf{ExSol} package}
\author{Philippe Marti}
\setlength{\parindent}{0em}
\begin{document}
\maketitle

\section{Gleichungssysteme und Geraden}

Ein bisschen Theorie\ldots

\begin{exerciseseries}[solsubrule=\hrule]{Gleichungssysteme}
\begin{exercise}
Die Summe zweier Zahlen ist 17 und ihre Differenz 7. Bestimme die
beiden Zahlen!
\end{exercise}
\begin{solution}
5 und 12
\end{solution}

```

```

\begin{exercise}
  Die Differenz einer Zahl und dem Dreifachen einer zweiten Zahl ist
  14. Bestimme die beiden Zahlen, falls die zweite Zahl ein Zehntel
  der ersten ist.
\end{exercise}
\begin{solution}
  20 und 2
\end{solution}
\end{exerciseseries}
~\\
Etwas mehr Theorie\ldots

\begin{exerciseseries}{Geraden}
  \begin{exercise}
    Berechne den Schnittpunkt von  $y=3x+1$  und  $y=3x-7$ .
  \end{exercise}
  \begin{solution}
    Es gibt keinen Schnittpunkt
  \end{solution}

  \begin{exercise}
    Die Familie Meier fordert Offerten für eine Heizungsreparatur
    ein. Firma A berechnet für die Fahrtkosten Fr. 42.- und für
    jede Arbeitsstunde 76.-. Bei der Firma B sind die Fahrtkosten
    Fr. 35.- und jede Arbeitsstunde wird mit Fr. 80.- berechnet.
    \begin{enumerate}[label=\alph*)]
      \item Welche Kosten entstehen für beide Firmen, wenn ein Monteur
        3.5 Stunden
        für die Arbeit benötigt? Welche Firma ist in diesem Fall
        kostengünstiger?

      \item Wie lauten die Gleichungen derjenigen zwei linearen
        Funktionen, die jeder Arbeitszeit  $x$  (in Stunden) die
        entstehenden Kosten  $y$  (in Franken) zuordnet?

      \item Berechne, bei welcher Arbeitszeit die Kosten bei beiden
        Firmen gleich sind.
    \end{enumerate}
  \end{exercise}
  \begin{solution}
    \begin{enumerate}[label=\alph*)]
      \item Firma A: 308.- | Firma B: 315.-
      \item A:  $y=76x+42$  | B:  $y=80x+35$ 
      \item Bei  $\frac{3}{4}$  Stunden
    \end{enumerate}
  \end{solution}
\end{exerciseseries}

\end{document}
%

```

3.3 Fiddling with the spacing

The default spacing provided by the ExSol package should be fine for most users. However, if you like to tweak, below you can find the controls.

As the formula collection generation is intended to interfere as little as possible with the flow of the main document, you will notice that it is impossible to control the extra spacing, as no extra spacing should originate from using the

`informulacollection` environment.

3.3.1 Spacing before and after the `exercises` environment

The lengths below control the spacing of the `exercises` environment:

- `exsolexerciseaboveskip`: rubber length controlling the vertical space after the top marker line of the environment
- `exsolexercisebelowskip`: rubber length controlling the vertical space before the bottom marker line of the environment

You can simply specify them like:

```
\setlength{\exsolexercisesaboveskip}{1ex plus 1pt minus 1pt}  
\setlength{\exsolexercisesbelowskip}{1ex plus 1pt minus 1pt}
```

The spacings specified here are the package defaults.

3.3.2 Spacing of the individual exercises

Caution: the spacing can only be tuned, when one invokes the `exerciseaslist` package option!

Then lengths below control the spacing of the `exercise` environment:

- `exercisetopbottomsep`: rubber length controlling the vertical space before and after individual exercises
- `exerciseleftmargin`: length controlling the horizontal space between the surrounding environment's left margin (most often the page margin) and the left edge of the exercise environment
- `exercisefrightmargin`: length controlling the horizontal space between the surrounding environment's right margin (most often the page margin) and the right edge of the exercise environment
- `exerciseitemindent`: length controlling the first-line indentation of the first paragraph in the exercise environment (actually, the label is set w.r.t. this position, that we will conveniently call position 'x')
- `exerciseparindent`: length controlling the first-line indentation of the other paragraphs in the exercise environment.
- `exerciselabelsep`: length controlling the distance between the label and position 'x'
- `exerciselabelwidth`: minimal width of the (internally right-aligned) box to use for the exercises label; if the box is not sufficiently big, position 'x' is shifted to the right

- `exerciseparsep`: internal paragraph separation (vertically)

You can simply specify them like:

```
\setlength{\exsolexercisetopbottomsep}{0pt plus 0pt minus 1pt}
\setlength{\exsolexercisefleftmargin}{1em}
\setlength{\exsolexerciserightmargin}{1em}
\setlength{\exsolexerciseparindent}{0em}
\setlength{\exsolexerciselabelsep}{0.5em}
\setlength{\exsolexerciselabelwidth}{0pt}
\setlength{\exsolexerciseitemindent}{0pt}
\setlength{\exsolexerciseparsep}{\parskip}
```

The spacings specified here are the package defaults.

3.4 Tips and tricks

If you want to include the solutions all at the end of the current document in global mode, you need to explicitly close the solution stream before including it:

```
\closeout\solutionstream\input{\jobname.sol.tex}
```

If you want to avoid exercises being split by a page boundary, then provide the package option 'minipage'. This causes the exercises to be wrapped in a minipage environment.

4 Implementation

```
1 (*package)
```

4.1 Auxiliary packages

The package uses some auxiliary packages:

```
2 \RequirePackage{ifmtarg}
3 \RequirePackage{fancyvrb}
4 \RequirePackage{ifthen}
5 \RequirePackage{kvoptions}
6 \RequirePackage{multicol}
7 \RequirePackage{varwidth}
8 \@ifpackageloaded{babel}{\typeout{Good: you loaded babel first!}}{\PackageError{exsol}{You fo
9     babel package before exsol}{}}
```

4.2 Package options

The package offers some options:

local This boolean option (true, false) allows setting the mode of the package into local, i.e. that the numbering of the exercises is not related to the position in the document, but uses it's own local counter in combination with a exerciseries counter.

```
10 \DeclareBoolOption[false]{local}
```

external This boolean option (true, false) allows setting the mode of the package into external, i.e. that the both exercises and solutions will be written to separate files.

```
11 \DeclareBoolOption[false]{external}
```

inline This boolean option (true, false) allows setting the mode of the package into inline, i.e. that the solutions will be included 'on the spot'.

```
12 \DeclareBoolOption[false]{inline}
```

nolabels This boolean option (true, false) allows suppressing the 'Exercise' and 'Solution' label that normally appear before the exercise and solution number.

```
13 \DeclareBoolOption[false]{nolabels}
```

exercisefontsize This option allows setting the font of the `exercises` environment. You may choose one of tiny, scriptsize, footnotesize, small, normalsize, large, etc. E.g., `[exercisefontsize=small]`.

```
14 \DeclareStringOption[normalsize]{exercisefontsize}
```


exerciseaslist This boolean option (true, false) allows setting the typesetting of the **exercises** in a list environment. This causes the exercises to be typeset in a more compact fashion, with indented left and right margin.

```
15 \DeclareBoolOption[false]{exerciseaslist}
```

copyexercisesinsolutions This boolean option (true, false) allows copying the exercises in the solutions file, to allow for making a complete stand-alone exercises bundle.

```
16 \DeclareBoolOption[false]{copyexercisesinsolutions}
```

minipage This boolean option (true, false) causes the exercises to be wrapped in minipages. This avoids them getting split by a page boundary.

```
17 \DeclareBoolOption[false]{minipage}
```

usesolutionserieslabels This boolean options (true,false) causes the exerciseries label to be reused when inserting the corresponding solutionseries.

```
18 \DeclareBoolOption[false]{usesolutionserieslabels}
```

The options are processed using:

```
19 \ProcessKeyvalOptions*
```

The options are subsequently handled

```
20 \newcommand{\exercisefontsize}{\csname \exsol@exercisefontsize\endcsname}
```

4.3 Customization of lengths

The commands below allow customizing many lengths that control the typesetting of the exercises.

First some lengths to control the spacing before and after **exercises**.

```
21 \newlength{\exsolexercisaboveskip}
22 \setlength{\exsolexercisaboveskip}{0ex plus 1pt minus 1pt}
23 \addtolength{\exsolexercisaboveskip}{-2\baselineskip}
24 \newlength{\exsolexercisbelowskip}
25 \setlength{\exsolexercisbelowskip}{0ex plus 1pt minus 1pt}
26 \addtolength{\exsolexercisbelowskip}{\baselineskip}
```

Then some lengths to control the spacing for a single exercise. These lengths only work when the **exerciseaslist** package option has been specified. Sensible defaults have been set.

```
27 \newlength{\exsolexercisetopbottomsep}
28 \setlength{\exsolexercisetopbottomsep}{0pt plus 0pt minus 1pt}
29 \newlength{\exsolexercisleftmargin}
```

```

30 \setlength{\exsolexerciseftrightmargin}{1em}
31 \newlength{\exsolexerciserightmargin}
32 \setlength{\exsolexerciserightmargin}{1em}
33 \newlength{\exsolexerciseparindent}
34 \setlength{\exsolexerciseparindent}{0em}
35 \newlength{\exsolexerciselabelsep}
36 \setlength{\exsolexerciselabelsep}{0.5em}
37 \newlength{\exsolexerciselabelwidth}
38 \setlength{\exsolexerciselabelwidth}{0pt}
39 \newlength{\exsolexerciseitemindent}
40 \setlength{\exsolexerciseitemindent}{0pt}
41 \newlength{\exsolexerciseparsep}
42 \setlength{\exsolexerciseparsep}{\parskip}

```

4.4 Con- and destruction of the auxiliary streams

At the beginning of your document, we start by opening a stream to a file that will be used to write the solutions to. At the end of your document, the package closes the stream.

```

43 \AtBeginDocument{
44   \typeout{Writing solutions to solution file \jobname.sol.tex}
45   \newwrite\solutionstream
46   \immediate\openout\solutionstream=\jobname.sol.tex
47   \ifxsol@external
48     \typeout{Writing exercises to exercise file \jobname.exc.tex}
49     \newwrite\exercisestream
50     \immediate\openout\exercisestream=\jobname.exc.tex
51   \else
52     \typeout{Using intermediate exercise file \jobname.exc.tex}
53     \newwrite\exercisestream
54   \fi
55   \typeout{Writing formulae to formula collection file \jobname.fc.tex}
56   \newwrite\formulacollectionstream
57   \immediate\openout\formulacollectionstream=\jobname.fc.tex
58   \typeout{Using intermediate formula file \jobname.for.tex}
59   \newwrite\formulastream
60 }
61 \AtEndDocument{
62   \immediate\closeout\formulacollectionstream
63   \immediate\closeout\solutionstream
64 }

```

In local mode we also want to close the solutionstream, read it and open it again:

```

65 \newcommand\loadSolutions{
66   \immediate\closeout\solutionstream
67   \input{\jobname.sol.tex}
68 %   \immediate\openout\solutionstream=\jobname.sol.tex
69 }

```

4.5 Series counter

By providing an exerciseries counter, proper numbering of the exercise series is provided. Note that separate series, render the numbering of the exercises from document-global, to series-local, therefore hindering the concordance of solutions to exercises.

```
70 \newcounter{exerciseries}[subsubsection]
71 \setcounter{exerciseries}{0}
72 \renewcommand{\theexerciseries}{\arabic{exerciseries}}
```

4.6 Exercise counter

By providing an exercise counter, proper numbering of the exercises is provided to allow for good cross referencing of the solutions to the exercises.

```
73 \newcounter{exercise}[exerciseries]
74 \setcounter{exercise}{0}
75 \renewcommand{\theexercise}{%
76   \ifxsol@local
77     \arabic{exerciseries}.\arabic{exercise}%
78   \else
79     \@ifundefined{c@chapter}{}{\if0\arabic{chapter}\else\arabic{chapter}.\fi}%
80     \if0\arabic{section}\else\arabic{section}\fi%
81     \if0\arabic{subsection}\else.\arabic{subsection}\fi%
82     \if0\arabic{subsubsection}\else.\arabic{subsubsection}\fi%
83     \if0\arabic{exercise}\else%
84     \@ifundefined{c@chapter}%
85     {\if0\arabic{section}\else-\fi}%
86     {-}%
87     \arabic{exercise}%
88   \fi
89 \fi
90 }
```

4.7 Detokenization in order to cope with utf8

Combining old-school L^AT_EX (before X_YL^AT_EX and Lua_T_EX) and UTF-8 is a pain. Detokenization has been suggested by Geoffrey Poore to solve issues with UTF-8 characters messing up the fancyvrb internals.

```
91 \newcommand{\GPES@write@detok}[1]{%
92   \immediate\write\exercisestream{\detokenize{#1}}}%
93 \newcommand{\GPSS@write@detok}[1]{%
94   \immediate\write\solutionstream{\detokenize{#1}}}%
95 \newcommand{\GPSS@write@detok}[1]{%
96   \GPES@write@detok{#1}%
97   \GPSS@write@detok{#1}}%
98 \newcommand{\GPFORCOL@write@detok}[1]{%
99   \immediate\write\formulacollectionstream{\detokenize{#1}}%
100  \immediate\write\formulastream{\detokenize{#1}}}%

```

```

101 \newcommand{\GPFORCOLONLY@write@detok}[1]{%
102   \immediate\write\formulacollectionstream{\detokenize{#1}}}%

```

5 The user environments

exercise The `exercise` environment is used to typeset your exercises, provide them with a nice label and allow for copying the exercise to the solutions file (if the package option `copyexercisesinsolution`) is set. The label can be set by redefining the `\exercisename` macro, or by relying on the Babel provisions. The code is almost literally taken from the `fancyvrb` package.

```

103 \def\exercise{\FV@Environment{}{exercise}}
104 \def\FVB@exercise{%
105   \refstepcounter{exercise}%
106   \ifexsol@external\else
107     \immediate\openout\exercisestream=\jobname.exc.tex
108   \fi
109   \ifexsol@local
110 %   \immediate\write\solutionstream{
111   \else
112 %   \immediate\write\solutionstream{\string\vspace*\string{2ex}\string}%
113 %   \string\quad\string\newline}
114   \fi
115   \ifexsol@copyexercisesinsolutions
116     \immediate\write\solutionstream{\string\begin{exsol@exercise}{\theexercise}}
117   \fi
118   \immediate\write\exercisestream{\string\begin{exsol@exercise}{\theexercise}}
119   \@bsphack
120   \begingroup
121     \FV@UseKeyValues
122     \FV@DefineWhiteSpace
123     \def\FV@Space{\space}%
124     \FV@DefineTabOut
125     \ifexsol@copyexercisesinsolutions
126       \let\FV@ProcessLine\GPSS@write@detok %
127     \else
128       \let\FV@ProcessLine\GPES@write@detok %
129     \fi
130     \relax
131     \let\FV@FontScanPrep\relax
132     \let\@noligs\relax
133     \FV@Scan
134   }
135 \def\FVE@exercise{
136   \endgroup\@esphack
137   \immediate\write\exercisestream{\string\end{exsol@exercise}}
138   \ifexsol@copyexercisesinsolutions
139     \immediate\write\solutionstream{\string\end{exsol@exercise}}
140   \fi
141   \ifexsol@external\else
142     \immediate\closeout\exercisestream
143   \input{\jobname.exc.tex}

```

```

144 \fi
145 }
146 \DefineVerbatimEnvironment{exercise}{exercise}{}

```

exsol@exercise The `exsol@exercise` environment is an internal macro used to typeset your exercises and provide them with a nice label and number. Do not use it directly. Use the proper environment `exercise` instead.

```

147 \newenvironment{exsol@exercise}[1]
148 {%
149 \ifthenelse{\boolean{exsol@minipage}}{\begin{minipage}[t]{\textwidth}}{%
150 \ifthenelse{\boolean{exsol@exerciseaslist}}
151 {
152 \begin{list}%
153 {}
154 {%
155 \setlength{\topsep}{\exsol@exercisetopbottomsep}%
156 \setlength{\leftmargin}{\exsol@exercisefleftmargin}%
157 \setlength{\rightmargin}{\exsol@exerciserightmargin}%
158 \setlength{\listparindent}{\exsol@exerciseparindent}%
159 \setlength{\itemindent}{\exsol@exerciseitemindent}%
160 \setlength{\parsep}{\exsol@exerciseparsep}%
161 \setlength{\labelsep}{\exsol@exerciselabelsep}%
162 \setlength{\labelwidth}{\exsol@exerciselabelwidth}%
163 \item[\ifexsol@nolabels~#1:\else\exercisename{~#1:\fi}%
164 }
165 {\ifexsol@nolabels #1:\else%
166 \subparagraph{\exercisename{~#1:}}\fi}
167 }
168 {%
169 \ifthenelse{\boolean{exsol@exerciseaslist}}{%
170 \end{list}}{%
171 \ifthenelse{\boolean{exsol@minipage}}{\end{minipage}}{\par}%
172 }

```

solution The `solution` environment is used to typeset your solutions and provide them with a nice label and number that corresponds to the exercise that preceded this solution. Theno label can be set by redefining the `\solutionname` macro, or by relying on the Babel provisions. The code is almost literally taken from the `fancyvrb` package.

```

173 \def\solution{\FV@Environment{}}{solution}}
174 \def\FVB@solution{%
175 % \typeout{Writing solution to \jobname.sol.tex}
176 % WDSC
177 \ifexsol@copyexercisesinsolutions
178 \immediate\write\solutionstream{\string\begin{exsol@solution}}{}
179 \else
180 \ifexsol@inline
181 \immediate\write\solutionstream{\string\begin{exsol@solution}}{}
182 \else
183 \immediate\write\solutionstream{\string\begin{exsol@solution}{\theexercise}}
184 \fi

```

```

185 \fi
186 % \ifexsol@copyexercisessolutions
187 % \immediate\write\solutionstream{\string\begin{exsol@solution}{}}
188 % \else
189 % \immediate\write\solutionstream{\string\begin{exsol@solution}{\theexercise}}
190 % \fi
191 \@bsphack
192 \begingroup
193 \FV@UseKeyValues
194 \FV@DefineWhiteSpace
195 \def\FV@Space{\space}%
196 \FV@DefineTabOut
197 \let\FV@ProcessLine\GPSS@write@detok %
198 \relax
199 \let\FV@FontScanPrep\relax
200 \let\@noligs\relax
201 \FV@Scan
202 }
203 \def\FVE@solution{
204 \endgroup\@esphack
205 \immediate\write\solutionstream{\string\end{exsol@solution}}
206 \ifexsol@inline
207 \immediate\closeout\solutionstream
208 \input{\jobname.sol.tex}
209 \immediate\openout\solutionstream=\jobname.sol.tex
210 \fi
211 }
212 \DefineVerbatimEnvironment{solution}{solution}{}

```

exsol@solution The `exsol@solution` environment is an internal macro used to typeset your solutions. Do not use it directly. Use the proper environment `solution` instead.

```

213 \newenvironment{exsol@solution}[1]
214 {%
215 \ifthenelse{\boolean{exsol@minipage}}{\begin{minipage}[t]{\textwidth}}{%
216 \ifthenelse{\boolean{exsol@exerciseaslist}}
217 {\begin{list}%
218 {%
219 }%
220 {%
221 \setlength{\topsep}{\exsol@exercisetopbottomsep}%
222 \setlength{\leftmargin}{\exsol@exercisefleftmargin}%
223 \setlength{\rightmargin}{\exsol@exerciserightmargin}%
224 \setlength{\listparindent}{\exsol@exerciseparindent}%
225 \setlength{\itemindent}{\exsol@exerciseitemindent}%
226 \setlength{\parsep}{\exsol@exerciseparsep}
227 \setlength{\labelsep}{\exsol@exerciselabelsep}
228 \setlength{\labelwidth}{\exsol@exerciselabelwidth}}
229 \item[\ifexsol@nolabels #1:\else%
230 \solutionname{}\@ifmtarg{#1}{-}{#1:\fi}
231 }%
232 {\ifexsol@nolabels #1:\else%
233 \subparagraph{\solutionname{}\@ifmtarg{#1}{-}{#1:\fi}

```

```

234 }
235 {%
236 \ifthenelse{\boolean{exsol@exerciseaslist}}{%
237 \end{list}}{}%
238 \ifthenelse{\boolean{exsol@minipage}}{\end{minipage}}{\par}%
239 }

```

exercises The **exercises** environment helps typesetting your exercises to stand out from the rest of the text. You may use it at the end of a chapter, or just to group some exercises in the text.

```

240 \define@key{exercises}{columns}{\renewcommand\columncount{#1}}
241 \define@key{exercises}{exsubrule}{\renewcommand\exsubrule{#1}}
242 \define@key{exercises}{solsubrule}{\renewcommand\solsubrule{#1}}
243 \define@key{exercises}{subrule}{\renewcommand\exsubrule{#1}\renewcommand\solsubrule{#1}}
244 \newenvironment{exercises}[1] []
245 {%
246 \newcommand\columncount{1}% default
247 \newcommand\exsubrule{}% default
248 \newcommand\solsubrule{}% default
249 \setkeys{exercises}{#1}%
250 \exercisefontsize\rule{.25\linewidth}{0.15mm}%
251 \vspace*{-1.5\baselineskip}%
252 \paragraph{\exercisename}\~\~*
253 \ifthenelse{\columncount > 1}{\begin{multicols}{\columncount}}{}%
254 }%
255 {
256 \ifthenelse{\columncount > 1}{\end{multicols}}{\relax}%
257 \vspace*{-\baselineskip}\vspace*{\exsolexercisesbelowskip}%
258 \exsubrule\par}

```

exerciseries The **exerciseries** environment helps typesetting your exercises in series.

```

259 \define@key{exerciseries}{columns}{\renewcommand\columncount{#1}}
260 \define@key{exerciseries}{exsubrule}{\renewcommand\exsubrule{#1}}
261 \define@key{exerciseries}{solsubrule}{\renewcommand\solsubrule{#1}}
262 \define@key{exerciseries}{subrule}{\renewcommand\exsubrule{#1}\renewcommand\solsubrule{#1}}
263 \newenvironment{exerciseries}[2] []
264 {
265 \refstepcounter{exerciseries}%
266 \newcommand\columncount{1} % default
267 \newcommand\exsubrule{} % default
268 \newcommand\solsubrule{} % default
269 \setkeys{exerciseries}{#1}%
270 \paragraph{\seriesname~\theexerciseries:~#2}~\par
271 \ifthenelse{\columncount > 1}{\begin{multicols}{\columncount}}{}
272 \ifexsol@inline\else
273 \immediate\write\solutionstream{\string\begin\string\solutionseries\string}%
274 \string[#1\string]\string[#2\string]\string{\theexerciseries\string}}
275 \fi
276 }
277 {
278 \ifthenelse{\columncount > 1}{\end{multicols}}{\relax}

```

```

279 \exsubrule\par
280 \ifexsol@inline\else
281   \immediate\write\solutionstream{\string\end\string{solutionseries\string}}
282 \fi
283 }

```

solutionseries The `solutionseries` environment helps typesetting your solutions in series. You don't need to use this function explicitly. The package does this for you.

```

284 \newenvironment{solutionseries}[3] []
285 {
286   \newcommand\columncount{1} % default
287   \newcommand\exsubrule{} % default
288   \newcommand\solsubrule{} % default
289   \setkeys{exercises}{#1}%
290   \paragraph{\seriesname~#3\ifexsol@usesolutionserieslabels: #2\fi}~\par
291   \ifthenelse{\columncount > 1}{\begin{multicols}{\columncount}}{}
292 }
293 {
294   \ifthenelse{\columncount > 1}{\end{multicols}}{}
295   \solsubrule\par
296 }

```

informulacollection The `informulacollection` environment is used to write its contents to the formula collection stream and load back into the main text for typesetting. The code is almost literally taken from the `fancyvrb` package.

```

297 \def\informulacollection{\FV@Environment{}{informulacollection}}
298 \def\FVB@informulacollection{%
299   \immediate\openout\formulastream=\jobname.for.tex
300   %\typeout{Writing formula to \jobname.for.tex and \jobname.fc.tex}
301   \@bsphack
302   \begingroup
303     \FV@UseKeyValues
304     \FV@DefineWhiteSpace
305     \def\FV@Space{\space}%
306     \FV@DefineTabOut
307     \let\FV@ProcessLine\GPFORCOL@write@detok %
308     \relax
309     \let\FV@FontScanPrep\relax
310     \let\@noligs\relax
311     \FV@Scan
312   }
313 \def\FVE@informulacollection{
314   \endgroup\@esphack
315   \immediate\closeout\formulastream
316   \input{\jobname.for.tex}
317 }
318 \DefineVerbatimEnvironment{informulacollection}{informulacollection}{}

```

informulacollectiononly The `informulacollectiononly` environment is used to write its contents to the formula collection stream *without* loading it back into the main text for typesetting.

The code is almost literally taken from the fancyvrb package.

```

319 \def\informatulacollectiononly{\FV@Environment}{\informatulacollectiononly}}
320 \def\FVB@informatulacollectiononly{%
321   \typeout{Writing special to \jobname.fc.tex}
322   \@bsphack
323   \begingroup
324     \FV@UseKeyValues
325     \FV@DefineWhiteSpace
326     \def\FV@Space{\space}%
327     \FV@DefineTabOut
328     \let\FV@ProcessLine\GPFORCOLONLY@write@detok %
329     \relax
330     \let\FV@FontScanPrep\relax
331     \let\@noligs\relax
332     \FV@Scan
333   }
334 \def\FVE@informatulacollectiononly{
335   \endgroup\@esphack
336 }
337 \DefineVerbatimEnvironment{informatulacollectiononly}{informatulacollectiononly}{}

```

5.1 Some Babel provisions

```

338 \newcommand{\exercisename}{Exercise}
339 \newcommand{\exercisesname}{Exercises}
340 \newcommand{\solutionname}{Solution}
341 \newcommand{\solutionsname}{Solutions}
342 \newcommand{\seriesname}{Series}

```

You may redefine these macros, but to help you out a little bit, we provide with some basic Babel auxiliaries. If you're a true polyglot and are willing to help me out by providing translations for other languages, I'm very willing to incorporate them into the code.

```

343 \addto\captionsdutch{%
344   \renewcommand{\exercisename}{Oefening}%
345   \renewcommand{\exercisesname}{Oefeningen}%
346   \renewcommand{\solutionname}{Oplossing}%
347   \renewcommand{\solutionsname}{Oplossingen}%
348   \renewcommand{\seriesname}{Reeks}%
349 }
350 \addto\captionsgerman{%
351   \renewcommand{\exercisename}{Aufgabe}%
352   \renewcommand{\exercisesname}{Aufgaben}%
353   \renewcommand{\solutionname}{L"osung}%
354   \renewcommand{\solutionsname}{L"osungen}%
355   \renewcommand{\seriesname}{Serie}%
356 }
357 \addto\captionsgerman{%
358   \renewcommand{\exercisename}{Aufgabe}%
359   \renewcommand{\exercisesname}{Aufgaben}%
360   \renewcommand{\solutionname}{L"osung}%

```

```

361 \renewcommand{\solutionsname}{L\osungen}%
362 \renewcommand{\seriesname}{Serie}%
363 }
364 \addto\captionsfrench{%
365 \renewcommand{\exercisename}{Exercice}%
366 \renewcommand{\exercisesname}{Exercices}%
367 \renewcommand{\solutionname}{Solution}%
368 \renewcommand{\solutionsname}{Solutions}%
369 \renewcommand{\seriesname}{Serie}%
370 }
371 \addto\captionsfinnish{
372 \renewcommand{\exercisename}{Teht\av"a}%
373 \renewcommand{\exercisesname}{Teht\avi"a}%
374 \renewcommand{\solutionname}{Ratkaisu}%
375 \renewcommand{\solutionsname}{Ratkaisut}%
376 \renewcommand{\seriesname}{Sarja}
377 }
378 \addto\captionsspanish{%
379 \renewcommand{\exercisename}{Ejercicio}%
380 \renewcommand{\exercisesname}{Ejercicios}%
381 \renewcommand{\solutionname}{Soluci'on}%
382 \renewcommand{\solutionsname}{Soluciones}%
383 \renewcommand{\seriesname}{Serie}%
384 }

```

Now the final hack overloads the basic sectioning commands to make sure that they are copied into your solution book.

```

385 \newif\ifnoexinchapter
386 \noexinchapterfalse
387 \ifexsol@local
388 \else
389 \ifx\chapter\@undefined\else
390 \let\exsol@@chapter\@chapter
391 \def\@chapter[#1]#2{%
392 \exsol@@chapter[#1]{#2}
393 \ifnoexinchapter
394 \noexinchapterfalse
395 \else
396 \addtocounter{chapter}{-1}
397 \immediate\write\solutionstream{\string\setcounter{chapter}{\arabic{chapter}}%
398 \string\chapter{#1}}%
399 \ifexsol@external
400 \immediate\write\exercisestream{\string\setcounter{chapter}{\arabic{chapter}}%
401 \string\chapter{#1}}%
402 \fi
403 \addtocounter{chapter}{1}
404 \fi
405 }
406 \fi
407
408 \ifdefined\frontmatter
409 \let\exsol@@frontmatter\frontmatter
410 \def\frontmatter{%

```

```

411 \immediate\write\solutionstream{\string\frontmatter}%
412 \ifexsol@external%
413 \immediate\write\exercisestream{\string\frontmatter}%
414 \fi%
415 \exsol@@frontmatter
416 }
417 \fi
418 \ifdefined\frontmatter
419 \let\exsol@@mainmatter\mainmatter
420 \def\mainmatter{%
421 \immediate\write\solutionstream{\string\mainmatter}%
422 \ifexsol@external%
423 \immediate\write\exercisestream{\string\mainmatter}%
424 \fi%
425 \exsol@@mainmatter
426 }
427 \fi
428 \ifdefined\backmatter
429 \let\exsol@@backmatter\backmatter
430 \def\backmatter{%
431 \immediate\write\solutionstream{\string\backmatter}%
432 \ifexsol@external%
433 \immediate\write\exercisestream{\string\backmatter}%
434 \fi%
435 \exsol@@backmatter
436 }
437 \fi
438 \ifdefined\appendix
439 \let\exsol@@appendix\appendix
440 \def\appendix{%
441 \immediate\write\solutionstream{\string\appendix}%
442 \ifexsol@external%
443 \immediate\write\exercisestream{\string\appendix}%
444 \fi%
445 \exsol@@appendix
446 }
447 \fi
448 \fi

```

`\noexercisennextchapter` If you have chapters without exercises, you may want to leave them out of your solution book. You can do this by putting the `\noexercisennextchapter` macro before your chapter mark.

```

449 \newcommand{\noexercisennextchapter}
450 {
451 \noexinchaptertrue
452 }

```

`\noexercisennextchapter` As an alternative you may just want to put this marker in your text to cause the printing of the sentence “No exercises in this chapter” in your solution book.

```

453 \newcommand{\noexercisennextchapter}
454 {
455 \immediate\write\solutionstream{No exercises in this chapter}

```

```

456 \ifexsol@external%
457 \immediate\write\exercisestream{No exercises in this chapter}%
458 \fi%
459 }

460 </package>

```

References

- [1] Timothy Van Zandt, Herbert Voß, Denis Girou, Sebastian Rahtz, Niall Mansfield The `fancyvrb` package. <http://ctan.org/pkg/fancyvrb>. online, accessed in January 2012.
- [2] The Comprehensive TeX Archive Network. <http://www.ctan.org>. online, accessed in January 2012.

Change History

v0.1		
General: Initial version	1	
v0.2		
General: Minor bug fixes based on		
first use by Paul Levrie	1	
Added option <code>exercisefont</code>	16	
Fixed babel errors	25	
Removed dash in counter when		
in document without		
sectioning commands	19	
exercises : Attempted to fix		
MiKTeX formatting problems	23	
exsol@exercise : Attempted to fix		
MiKTeX formatting problems	21	
v0.3		
General: Minor bug fixes based on		
second use by Paul	1	
exercises : Added some extra		
whitespace below		
<code>exercisename</code>	23	
exsol@exercise : Fixed <code>labelsep</code> to		
avoid cluttered <code>itemize</code>		
environments	21	
v0.4		
General: Allowed for non-list		
formatting of exercises (as		
default)	1	
Added option <code>exerciselinlist</code>	17	
Changed name of option to		
<code>exercisefontsize</code>	16	
		exsol@exercise : Added option
		<code>exerciselinlist</code> such that default
		results in non list formatting of
		<code>exercise</code>
		21
	v0.5	
	General: Added option to also	
	send exercises to solutions file	1
	Added option	
	<code>copyexercisinsolutions</code>	17
	Changed option <code>exerciselinlist</code>	
	to <code>exerciseaslist</code>	17
	exsol@exercise : Changed	
	implementation to allow for	
	copying the exercises to the	
	solutions file.	21
	v0.6	
	General: Prepared for CTAN	
	publication	1
	v0.7	
	General: Fixed UTF8	
	compatibility issues	1
	Added detokenized writing	19
	Added Finnish language support	25
	v0.8	
	General: Fixed missing babel tag	
	and running out of write	
	handles	1
	moved <code>newwrite</code> of exercise	
	stream to this spot to avoid	
	consuming all handles	18

v0.9	General: . Changed default behavior w.r.t. minipage-wrapping of exercises . 17	Completed German language support (i.e. new spelling ngerman) support 25
	Changed default behavior w.r.t. minipage-wrapping of exercises 1	exercises: Added multicolumn feature 23
v0.91	General: Corrected minipage dependence, made 1	v1.3
	added user-accessible lengths . . 17	General: Correction of spacings and counters 1
v1.0	General: First stable release 1	Added macro to suppress chapter in solution stream . . . 26
	Added congruence of chaptercounter of main document and chapter counter of exercises document 26	Corrected counter in solutionstream 26
	Added detokenized writing of formula and formula collection stream 19	exsol@exercise: Corrected formatting error in case of options exerciselist 21
v1.1	General: Bugfix release 1	v1.4
	Corrected congruence of chaptercounter of main document and chapter counter of exercises document (taking into account alphanumbered chapters 26	General: . Implemented option to display solutionserieslabels when option 'usersolutionserieslabels' is true 24
v1.2	General: Implemented multicolumn option for exercises, introduced new options (local, nolabels), separate counter for exerciseries (only for use local mode), introduced local mode . 1	. added 'usesolutionserieslabels' option 17
	Added exerciseries environment 23	Allowed for adding exerciseries label in solutionseries using option 'usesolutionserieslabels' 1
	Added option local 16	v1.5
	Added option nolabels 16	General: Added inline and external mode 1
	Added series counter 19	Added option external 16
	Added solutionseries environment 24	Added option inline 16
	Added Spanish language support 25	Added writing the sectioning code to the exercise stream in external mode 26
		v1.6
		General: Added check to see if babel was loaded, and issue appropriate error 1
		v1.7
		General: Ensured compatibility with spelatex package 1
		Changed makechapterhead into @chapter to avoid incompatibility with spelatex . 26

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in **roman** refer to the code lines where the entry is used.

Symbols 360, 361, 372, 373
 \" 353, 354,

\'	381	259, 266, 271,	107, 118, 137,
\@bsphack		278, 286, 291, 294	142, 400, 413,
. 119, 191, 301, 322		\copyexercisinsolutions	423, 433, 443, 457
\@chapter	390, 391	 16	\exsol@@appendix ..
\@esphack		\csname	 439, 445
. 136, 204, 314, 335			\exsol@@backmatter
\@ifmtarg	230, 233	D	 429, 435
\@ifpackageloaded	8	\DeclareBoolOption	\exsol@@chapter 390, 392
\@ifundefined	79, 84	 10, 11, 12,	\exsol@@frontmatter
\@noligs		13, 15, 16, 17, 18	 409, 415
. 132, 200, 310, 331		\DeclareStringOption 14	\exsol@@mainmatter
\@undefined	389	\def	 419, 425
\\	252	 103, 104,	\exsol@exercise ... 147
		123, 135, 173,	\exsol@exercisefontsize
A		174, 195, 203,	 20
\addto	343, 350,	297, 298, 305,	\exsol@solution ... 213
357, 364, 371, 378		313, 319, 320,	\exsol@exerciseitemindent
\addtocounter	396, 403	326, 334, 391,	.. 39, 40, 159, 225
\addtolength	23, 26	410, 420, 430, 440	\exsol@exerciselabelsep
\appendix	438,	\define@key ... 240,	.. 35, 36, 161, 227
439, 440, 441, 443		241, 242, 243,	\exsol@exerciselabelwidth
\arabic	72, 77,	259, 260, 261, 262	.. 37, 38, 162, 228
79, 80, 81, 82,		\DefineVerbatimEnvironment	\exsol@exerciseleftmargin
83, 85, 87, 397, 400		. 146, 212, 318, 337	.. 29, 30, 156, 222
\AtBeginDocument	43	\detokenize	\exsol@exerciseparindent
\AtEndDocument	61		.. 33, 34, 158, 224
		92, 94, 99, 100, 102	\exsol@exerciseparsep
B		E	.. 41, 42, 160, 226
\backmatter	428,	\else . 51, 78, 79, 80,	\exsol@exerciserightmargin
429, 430, 431, 433		81, 82, 83, 85,	.. 31, 32, 157, 223
\baselineskip		106, 111, 127,	\exsol@exercisesaboveskip
.. 23, 26, 251, 257		141, 163, 165,	 21, 22, 23
\begin	116, 118,	179, 182, 188,	\exsol@exercisesbelowskip
149, 152, 178,		229, 232, 272,	... 24, 25, 26, 257
181, 183, 187,		280, 388, 389, 395	\exsol@exercisetopbottomsep
189, 215, 217,		\end 137, 139, 170, 171,	.. 27, 28, 155, 221
253, 271, 273, 291		205, 237, 238,	\exsubrule 241, 243,
\begingroup		256, 278, 281, 294	247, 258, 260,
. 120, 192, 302, 323		\endcsname	262, 267, 279, 287
\boolean	149,	 20	\external 11
150, 169, 171,		\endgroup	
215, 216, 236, 238		. 136, 204, 314, 335	
C		\exercise	 103, 103
\captionsdutch	343	\exerciseaslist	 15
\captionsfinnish	371	\exercisename	
\captionsfrench	364	 163, 166,	F
\captionsgerman	350	338, 344, 351,	\fi 54, 79,
\captionsngerman	357	358, 365, 372, 379	80, 81, 82, 85,
\captionsspanish	378	\exercises	88, 89, 108, 114,
\chapter	389, 398, 401	 240	117, 129, 140,
\closeout	62,	\exerciseseries	144, 163, 166,
63, 66, 142, 207, 315		... 259	184, 185, 190,
\columncount	240,	\exercisefontsize	210, 230, 233,
246, 253, 256,		 14, 20, 250	275, 282, 290,
		\exercisesname	402, 404, 406,
		. 252,	414, 417, 424,
		339, 345, 352,	427, 434, 437,
		359, 366, 373, 380	444, 447, 448, 458
		\exercisestream	
		..	
		. 49, 50, 53, 92,	

\formulacollectionstream	56, 57, 62, 99, 102	\ifexsol@external .	 47, 106,	\let	 126, 128,
\formulastream			141, 399, 412,		131, 132, 197,
. 59, 100, 299, 315			422, 432, 442, 456		199, 200, 307,
\frontmatter	408, 409,	\ifexsol@inline .			309, 310, 328,
410, 411, 413, 418		. 180, 206, 272, 280			330, 331, 390,
\FV@DefineTabOut .		\ifexsol@local		\linewidth	 250
. 124, 196, 306, 327		 76, 109, 387		\listparindent	158, 224
\FV@DefineWhiteSpace		\ifexsol@nolabels .		\loadSolutions	 65
. 122, 194, 304, 325		. 163, 165, 229, 232		\local	 10
\FV@Environment .		\ifexsol@usesolutionserieslabels			
. 103, 173, 297, 319		 290		M	
\FV@FontScanPrep .		\ifnoexinchapter .		\mainmatter	
. 131, 199, 309, 330		 385, 393		. 419, 420, 421, 423	
\FV@ProcessLine	126,	\ifthenelse .	149,	\minipage	 17
128, 197, 307, 328		150, 169, 171,			
\FV@Scan		215, 216, 236,		N	
. 133, 201, 311, 332		238, 253, 256,		\newcounter	 70, 73
\FV@Space		271, 278, 291, 294		\newif	 385
. 123, 195, 305, 326		\ifx	 389	\newlength	 21,
\FV@UseKeyValues .		\immediate .	46, 50,	24, 27, 29, 31,	
. 121, 193, 303, 324		57, 62, 63, 66,		33, 35, 37, 39, 41	
\FVB@exercise	 104	68, 92, 94, 99,		\newline	 113
\FVB@informulacollection		100, 102, 107,		\newwrite	
..... 298		110, 112, 116,		. 45, 49, 53, 56, 59	
\FVB@informulacollectiononly		118, 137, 139,		\noexerciseshapter	
..... 320		142, 178, 181,		 453	
\FVB@solution	 174	183, 187, 189,		\noexerciseshapter	
\FVE@exercise	 135	205, 207, 209,		 449, 453	
\FVE@informulacollection		273, 281, 299,		\noexinchapterfalse	
..... 313		315, 397, 400,		 386, 394	
\FVE@informulacollectiononly		411, 413, 421,		\noexinchaptertrue	451
..... 334		423, 431, 433,		\nolabels	 13
\FVE@solution	 203	441, 443, 455, 457			
		\informulacollection		O	
		 297, 297		\openout	 46, 50,
G		\informulacollectiononly		57, 68, 107, 209, 299	
\GPES@write@detok .		 319, 319			
..... 91, 96, 128		\inline	 12	P	
\GPES@write@detok		\input .	67, 143, 208, 316	\PackageError	 8
..... 95, 126		\item	 163, 229	\par	. 171, 238, 258,
\GPFORCOL@write@detok		\itemindent .	159, 225	270, 279, 290, 295	
..... 98, 307				\paragraph	252, 270, 290
\GPFORCOLONLY@write@detok				\parsep	 160, 226
..... 101, 328				\parskip	 42
\GPSS@write@detok .		J		\ProcessKeyvalOptions	
..... 93, 97, 197		\jobname	44, 46, 48, 50,	 19	
		52, 55, 57, 58,			
		67, 68, 107, 143,		Q	
I		175, 208, 209,		\quad	 113
\if	79, 80, 81, 82, 83, 85	299, 300, 316, 321			
\ifdefined				R	
. 408, 418, 428, 438				\refstepcounter	105, 265
\ifexsol@copyexercisesinsolutions		L		\relax	 130,
..... 115,		\labelwidth .	161, 227	131, 132, 198,	
125, 138, 177, 186		\leftmargin .	162, 228		
		156, 222			

199, 200, 256,	158, 159, 160,	400, 401, 411,
278, 308, 309,	161, 162, 221,	413, 421, 423,
310, 329, 330, 331	222, 223, 224,	431, 433, 441, 443
<code>\renewcommand</code>	225, 226, 227, 228	<code>\subparagraph</code> . 166, 233
... 72, 75, 240,	<code>\solsubrule</code> ... 242,	T
241, 242, 243,	243, 248, 261,	<code>\textwidth</code> ... 149, 215
259, 260, 261,	262, 268, 288, 295	<code>\theexercise</code> ... 75,
262, 344, 345,	<code>\solution</code> 173, 173	116, 118, 183, 189
346, 347, 348,	<code>\solutionname</code>	<code>\theexerciseries</code>
351, 352, 353,	... 230, 233,	... 72, 270, 274
354, 355, 358,	340, 346, 353,	<code>\topsep</code> 155, 221
359, 360, 361,	360, 367, 374, 381	<code>\typeout</code> 8, 44, 48, 52,
362, 365, 366,	<code>\solutionseries</code> ... 284	55, 58, 175, 300, 321
367, 368, 369,	<code>\solutionsname</code>	U
372, 373, 374,	. 341, 347, 354,	<code>\usesolutionserieslabels</code>
375, 376, 379,	361, 368, 375, 382	... 18
380, 381, 382, 383	<code>\solutionstream</code>	V
<code>\RequirePackage</code> ...	... 45, 46, 63,	<code>\vspace</code> ... 112, 251, 257
... 2, 3, 4, 5, 6, 7	66, 68, 94, 110,	W
<code>\rightmargin</code> . 157, 223	112, 116, 139,	<code>\write</code> ... 92, 94, 99,
<code>\rule</code> 250	178, 181, 183,	100, 102, 110,
S	187, 189, 205,	112, 116, 118,
<code>\seriesname</code> 270, 290,	207, 209, 273,	137, 139, 178,
342, 348, 355,	281, 397, 411,	181, 183, 187,
362, 369, 376, 383	421, 431, 441, 455	189, 205, 273,
<code>\setcounter</code>	<code>\space</code> 123, 195, 305, 326	281, 397, 400,
.. 71, 74, 397, 400	<code>\string</code> ... 112, 113,	411, 413, 421,
<code>\setkeys</code> .. 249, 269, 289	116, 118, 137,	423, 431, 433,
<code>\setlength</code> .. 22, 25,	139, 178, 181,	441, 443, 455, 457
28, 30, 32, 34,	183, 187, 189,	
36, 38, 40, 42,	205, 273, 274,	
155, 156, 157,	281, 397, 398,	